

UTM Wireless Protection

Get secure and reliable wireless access all over the office

Simplify your wireless networking by using Sophos UTM as a wireless controller to centralize your Wi-Fi management and security. Our access points are automatically set up and configured by the UTM. That means all your wireless clients get complete threat protection too.



Highlights

- ▶ Support for the latest high-speed wireless standards including 802.11ac and 802.11n
- ▶ Centrally controlled wireless from your UTM
- ▶ No local configuration of access points required
- ▶ Automated channel optimization for maximum performance
- ▶ Complete UTM protection for wireless clients
- ▶ Quick voucher-based guest access customizable with your brand
- ▶ Choose from a range of access-point and firewalls with integrated wireless
- ▶ Supports Microsoft Lync and VoIP

Installs fast with automatic setup and configuration

You can set up multiple wireless Access Points (APs) within minutes. They require no local configuration and will simply find the controller, retrieve their IP address via DHCP, and import the configuration. Devices automatically appear in the UTM interface where you can manually activate them.

Creates reliable networks for all areas

Our range of access points support a variety of deployment scenarios. They include the desktop AP 15 and AP 55, the ceiling-mounted AP 30, the dual-band/dual-radio AP 50 and AP 100 and the outdoor AP 100X. The AP 50 can act as a wireless repeater and/or bridge to extend coverage to areas that are hard to reach with wired Ethernet.

Provides guest Wi-Fi and BYOD access

We give you secure, easy-to-manage guest access out-of-the-box—without extra appliances, licenses or complex configuration. And you can tailor the guest experience to suit your needs. Set bandwidth limits and content filtering as well as customizing the login page and vouchers to strengthen your company brand.

Secure wireless and integrated UTM protection

To prevent unauthorized access we use the most advanced encryption and authentication standards available, including WPA2-Enterprise in combination with IEEE 802.1X (RADIUS authentication). And, our APs forward wireless traffic to the UTM, giving wireless clients the same level of security as if they were physically connected to the LAN. You can also choose to authenticate users based on their credentials from any back end server supported by our UTM for greater flexibility and control.

"What I really like about Sophos' integrated wireless protection approach is that it frees our administrators from separately managing an expensive enterprise wireless solution."

Jason Richards, CEO, Vineyard Networks

Choose your Access Point

Our APs are built on the latest enterprise-class, high-speed wireless chipsets with custom designed antennas, added CPU and memory resources, and hardware accelerated encryption.



Technical Specifications

Sophos Access Points	AP 15	AP 30	AP 50	AP 55	AP 100	AP 100X
Capacity						
	SOHO	Ceiling mounted, for larger offices	Dual-band/dual-radio, high-density WLAN environments	Enterprise dual-band/dual-radio	Enterprise dual-band/dual-radio	IP67 Enterprise outdoor/exterior wall-mount
Maximum throughput	300 Mbps	300 Mbps	300 Mbps	867 Mbps + 300 Mbps	1.3 Gbps + 450 Mbps	1.3 Gbps + 450 Mbps
Multiple SSIDs	8	8	8 per radio (16 in total)	8 per radio (16 in total)	8 per radio (16 in total)	8 per radio (16 in total)
Technical Specification						
LAN interface	1 x 10/100/1000 Base TX	1 x 10/100 Base TX	1 x 10/100/1000 Base TX	1 x 10/100/1000 Base TX	1 x 10/100/1000 Base TX	1 x 10/100/1000 Base TX
Supported WLAN Standards	802.11 b/g/n 2.4 GHz	802.11 b/g/n 2.4 GHz	802.11 a/b/g/n 2.4 and 5 GHz	802.11 a/b/g/n/ac 2.4 and 5 GHz	802.11 a/b/g/n/ac 2.4 and 5 GHz	802.11 a/b/g/n/ac 2.4 and 5 GHz
DFS/TPC	-	-	-	Yes	Yes	Yes
Power over Ethernet	802.3at (PoE+)	802.3af	802.3at (PoE+)	802.3at (PoE+)	802.3at (PoE+)	802.3at (PoE+)
Number of antennas	2 external	2 internal	2 external	2 external	3 external	6 external
Number of radios	1	1	2	2	2	2
MIMO capabilities	2x2:2	2x2:2	2x2:2	2x2:2	3x3:3	3x3:3
Power supply	90-240V, 50/60 Hz	90-240V, 50/60 Hz	100-240V, 50/60 Hz	100-240V, 50/60 Hz	100-240V, 50/60 Hz	100-240V, 50/60 Hz
Power consumption (max.)	2.5W	8W	9.6W	11W	13W	15W
Physical Specification						
Dimensions (WxHxD)	194 x 32 x 115 mm	120 x 50 x 120 mm	217 x 28 x 139 mm	183 x 36 x 183 mm	183 x 36 x 183 mm	255 x 225 x 90 mm
Weight	260g	230g	390g	500g	505g	2.5 kg
Mounting options	Desktop/wall	Desktop/ceiling	Desktop/wall	Desktop/wall	Desktop/wall	Wall/pole
Regulatory compliance						
Certifications	FCC, CE, SRRC	FCC, CE, MIC, VCCI, NCC	FCC, CE, MIC, VCCI, NCC	FCC, CE	FCC, CE	FCC, CE, UL

Sophos UTM certifications



Common Criteria certified



Required subscriptions

UTM Wireless Protection. This is included if you subscribe to our BasicGuard or FullGuard UTM licenses.

Try it now for free

Register for a free 30-day evaluation at sophos.com/try-utm

United Kingdom and Worldwide Sales
Tel: +44 (0)8447 671131
Email: sales@sophos.com

North American Sales
Toll Free: 1-866-866-2802
Email: nasales@sophos.com

Australia and New Zealand Sales
Tel: +61 2 9409 9100
Email: sales@sophos.com.au

Asia Sales
Tel: +65 62244168
Email: salesasia@sophos.com